

pressurized systems and gas pressure testing for the telecommunications industry.



FEATURES

- Identifies gas and air leaks quickly
- Bubbles when exposed to gas leaks
- Meets or exceeds strict Telco performance specs
- No ethylene glycol
- Nontoxic, nonhazardous
- All-weather formula
- Nonflammable
- Available in ready-to-use and concentrated formula

DILUTION RATE

 $10^{\circ}F - 20^{\circ}F = I$ Gallon concentrate with I gallon of tap water. Above $20^{\circ}F = I$ Gallon concentrate with 2 gallons of tap water.

PACKAGE Net Fill

16 fl. oz. (.473 liters) I gal. (3.78 liters) Concentrate

APPLICATIONS

- Air Locks
- Air Pipes
- Air Tools
- Air Hose
- Compressors

PROPERTIES

Appearance / Physical State: Clear liquid with moderate viscosity

Evaporation Rate (Water = 1): >1 Halogen Content: None

HMIS: 1.1.0 pH: 6 – 8

Fittings and Connectors

Gas Appliances

Lead Cable Sheath

Natural Gas Meters

Pneumatic Pipe and Ducts

Solubility in Water: Soluble

- **Propane Tanks**
- Polyethylene Cable Sheath
- Refrigeration Equipment
- Sleeves & Splice Cases

Specific Gravity: 1.02 - 1.05**Temperature Range:** 10°F or higher Vapor Density (Air = 1): >1

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2009 LPS Laboratories * LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2225 • Rev. 3/2009

61016 61006

Part No.