



CONDEX

# SINGLE ROLLER CABLE BLOCKS

## Single Roller Cable Block

Support a single coaxial, fiber optic or copper cable or aerial innerduct up to 2.75" (70 mm) outside diameter with Condux Single Roller Cable Blocks. A built-in strand lock fits up to 3/8" (10 mm) strand to prevent creeping. The lock will be released when struck by a Cable Block Pusher ahead of a Cable Lasher. Frames are durable cast aluminum or molded plastic with steel inserts on strand contact surfaces. Rollers are plastic or aluminum.

Single Roller Cable Blocks may be equipped with a steel cable retainer to keep the cable or innerduct on the roller, even in low-tension situations.

Replacement rollers available. See page 14 for ordering information.



### FYI

Prior to Ordering Always Know the Following:

- Cable Diameter & Strand Diameter
- Max Cable O.D. 2.75" (70 mm)
- Max Strand Dia. 3/8" (10 mm)

No poly-based rope is to be used on plastic rollers. If you are using poly rope, please order aluminum block rollers.

Part Number	Description	Roller/Cable Config.	Frame Material	Roller Material
18000600	Single roller cable block	1 @ 2.75" (70 mm)	plastic	plastic
18001200	Single roller cable block with cable retainer	1 @ 2.75" (70 mm)	plastic	plastic
18000660	Single roller cable block	1 @ 2.75" (70 mm)	aluminum	plastic
18001260	Single roller cable block with cable retainer	1 @ 2.75" (70 mm)	aluminum	plastic
18000670	Single roller cable block	1 @ 2.75" (70 mm)	aluminum	aluminum
18001270	Single roller cable block with cable retainer	1 @ 2.75" (70 mm)	aluminum	aluminum



Cable Block 18000600



Cable Block 18001200



Cable Block 18000660



Cable Block 18001260



Cable Block 18000670



Cable Block 18001270