

Aluminum Split Bells


Plugs into conduit in manhole wall, guiding cable safely into the conduit regardless of the pulling angle.

Part Number	Size		Tube Length		Tube I.D.		Tube OD	
	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)
08041520	2	51	8	203	1.625	41	1.875	48
08041530	3	76	8	203	2.625	67	2.875	73
08041535	3½	89	8	203	3.125	79	3.375	88
08041540	4	102	8	203	3.625	92	3.875	98
08041550	5	127	8	203	4.625	117	4.875	124
08041560	6	152	8	203	5.625	143	5.875	149
08041564	6	152	12	304	5.625	143	5.875	149
08041570	8	203	12	304	7.875	200	7.500	191
08041515	4	102	15	381	3.625	92	3.875	98
08041518	4	102	18	457	3.625	92	3.875	98



Replacement Sheaves

Refer to this chart for specifications on sheave sizes for these products: 10,000 lb. Hooked Hanger Sheave, 4,000 lb. Hooked Hanger Sheave, Cable Feeding Sheave, Corner Cable Guide, Heavy Duty Quadrant Block, Fiber Optic Quad Block, Fiber Optic Hanger Block, 3 Sheave Cable Guide, Fiber Optic Sheave Mount, Overhead and Underground Fiber Optic Cable Sheave and Jamb Skid.



POWER CABLE INSTALLATION

Sheaves Specifications

Part Number	Nylatron® Part Number	Sheave Size		Maximum Cable O.D. A		Min. Bending Radius B		Max. Sheave Width C		Maximum Sheave O.D. D		Shaft Dia. E	
		(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)
08539308	08539304	1 x 3	25 x 76	1.50	38	.75	19	3.00	76	3.00	76	.62	15
08539036	08539037	3 x 7	76 x 178	3.00	76	2.25	57	3.72	94	7.00	203	1.25	32
08539136	08539137	4 x 7	102 x 178	4.00	102	2.25	57	4.31	109	7.00	203	1.25	32
08539236	08539237	5 x 7	127 x 178	5.00	127	2.25	57	5.13	130	7.00	203	1.25	32
08046611	08046612	3 x 11	76 x 279	3.00	76	4.25	107	3.75	95	11.00	279	1.25	32
08046711	08046712	4 x 11	102 x 279	4.00	102	3.75	95	4.75	120	11.00	279	1.25	32
08046811	08046812	5 x 11	127 x 279	5.00	127	3.25	82	5.75	146	11.00	279	1.25	32
08087811	08087812	6 x 11	152 x 279	6.00	152	3.12	79	6.75	171	11.00	279	1.25	32
08087911	08087912	8 x 11	203 x 279	8.25	209	2.75	69	8.75	222	11.00	279	1.25	32
08065411		4 x 20	102 x 508	4.25	107	8.50	215	4.75	120	20.00	508	1.25	32
08042911		5 x 20	127 x 508	5.00	127	8.00	203	5.75	146	20.00	508	1.25	32
08637743		3 x 24	76 x 610	1.38	35	11.12	282	4.00	102	24.12	613	1.00	25
08043011		5 x 26½	127 x 673	5.00	127	11.31	287	5.75	146	26.50	376	1.25	32

4,000 lb Sheaves

Part Number	Nylatron® Part Number	Sheave Size		Maximum Cable O.D. A		Min. Bending Radius B		Max. Sheave Width C		Maximum Sheave O.D. D		Shaft Dia. E	
		(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)
08042612		5 x 11	127 x 279	5.00	127	3.25	82	5.88	149	11.00	279	1.25	32
08042621		5 x 20	127 x 508	5.00	127	8.00	203	5.88	149	20.00	508	1.25	32
08042627		5 x 26½	127 x 673	5.00	127	11.31	287	5.75	146	26.50	673	1.25	32
08042651		8 x 26	203 x 660	8.00	203	11.25	286	8.50	216	26.00	660	1.25	32

☐ = Nylatron® Replacement Sheaves or Nylatron® Products.

NOTE: Nylatron® is a registered trademark of DSM.