



FIBER OPTIC CABLE PULLER TRAILER

CONDEX



Open Style Fiber Optic Cable Puller Trailer



Access job sites with ease using the Condux Open Style Fiber Optic Cable Puller Trailer. The open style has advantages in portability, accessibility and cost.

On the job, gain easy access to all components with the open face design. Small items can be stored in a lockable storage compartment. Leveling and stabilizing hardware is included. The Open Face Fiber Optic Cable Puller Trailer comes standard with a detachable cable puller remote mounting stand as well as built-in cable puller mounts on the left and right rear corners.

Options include a choice of three Condux Fiber Optic Cable Puller packages, choice of three capstans and a 16 HP (11.9 kW) Power Pack. The trailer bed is designed to accommodate standard and optional equipment with built-in mounting systems for secure travel.



Build your own Open Style Fiber Optic Cable Puller Trailer Kit

Use a **Base Part Number** shown below and also indicate accessory options by part number when placing your order. All items priced individually.



FYI
Not fully assembled trailer. Fiber puller and capstan ship separately.

Base Part No. Description
08675675 Open Style Fiber Optic Cable Pulling Trailer

(Includes: Trailer Flat Assembly, Remote Mounting Stand, 16 HP Power Pack, Wheel Chocks and Tool Box)

*Some assembly required

NOTE: Must purchase a Fiber Optic Cable Puller Option along with a Capstan Option from below.

Fiber Optic Cable Puller Options

(Includes Foot Control and Hoses)

| Part No. | Description |
|----------|---|
| 08690001 | Fiber Optic Cable Puller without Electronics |
| 08690055 | Fiber Optic Cable Puller with Electronic Control Box and Paperless Chart Recorder |

Capstan Options

| Part No. | Description |
|----------|--|
| 08675230 | 30" (762 mm) Capstan; 4" (102 mm) wide |
| 08675430 | 30" (762 mm) Capstan; 8" (203 mm) wide |
| 08675436 | 42" (1,067 mm) Capstan |
| 08675220 | 50" (1,270 mm) Capstan |



FIBER CABLE INSTALLATION

FIBER OPTIC CABLE PULLER TRAILER



Accessible storage; all components are easy to see and use

3 Capstan sizes available

Remote Mounting Stand (detachable)

2 1/2 inch (64 mm) square mounting socket for use with any Fiber Optic Cable Puller

Trailer weighs 950 lbs. (431 kg) (without options)

Briggs & Stratton 16 hp (11.9 kW) gasoline driven hydraulic power unit available



| Power Supply | |
|---------------|---|
| Engine | Briggs & Stratton V-Twin Vanguard OHV gas |
| Horsepower | 16 h.p. @ 3,600 RPM (11.9 kW @ 3,600 RPM) |
| Starting | Electric |
| Fuel | Unleaded Gas, 85 Octane min., 10% or less ethanol blend |
| Fuel Capacity | 5.0 gallons (18.9 liters) |
| Speed Control | Variable |

| Hydraulics | |
|---------------------------------|---|
| Capacity | 8.2 gpm @ 2,000 psi (31.0 lpm @ 138 bar) |
| Reservoir | 5.0 gallons (18.9 liters) |
| Filtration | 10 micron return line canister type |
| Hydraulic Oil Requirements | Petro based, anti-wear, high viscosities over 140 |
| Hydraulic Relief Valve Pressure | 2,150 psi (148.3 bar) |

| Trailer Specifications | |
|---------------------------------|---------------------------------|
| Weight (without puller) | 950 lbs (431 kg) |
| Axle | 3,500 lbs (1,590 kg) Type II |
| Tire | P205/75R14 Steel Belted Radials |
| Rims | 14" x 6" (356 mm x 152 mm) |
| Track | 60" (1,254 mm) |
| Overall Width | 80" (2,032 mm) |
| Overall Height (without puller) | 51" (1,295 mm) |
| Hitch | 3" (76 mm) Lunette Eye |
| Lighting | 7 Pin Connector |
| Electronics | 12 VDC |

FIBER CABLE
INSTALLATION