



PF[®]-141 IG

INDUSTRIAL GRADE SOLVENT



NSN 6850-01-423-2713

PACKAGE

Net Fill

55 gallons (208 liters)

Part No.

62855

APPLICATIONS

- Bearings
- Cables
- Chains
- Controls
- Gauges
- Gears
- Heavy Equipment
- High Voltage Cable Connections

FEATURES

- Removes petroleum based oils such as stamping oils, cutting fluids, rust inhibitors, and cable pulling lubricants
- Flash point above 140°F (60°F)
- No ozone depletion potential
- Replaces chlorinated solvents
- Excellent for use in parts washers
- Low residue
- Will not attack most commercial resins, plastics, urethanes, and synthetic rubbers
- Non-corrosive to metals such as copper, aluminum, magnesium, and stainless steel
- Qualified Products List for MIL-PRF-680 Type II



PROPERTIES

Appearance/Physical State:

Clear liquid

Boiling point:

366°F - 406°F (186°C - 208°C)
@ 760 mmHg

Evaporation Rate:

4.0 (Butyl Acetate=1)

Flammable Limits (estimated):

Lower: 1.3%, Upper: 8.8%

Flash Point:

147°F (64°C) TCC

Specific Gravity (water=1):

0.77 @ 68°F(20°C)

Vapor Pressure:

< 5 mmHg at 68°F(20°C)

VOC Content:

769 g/L

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE: WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2009 LPS Laboratories • LPS[®], PT[®] and PF[®] are registered trademarks of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2184 • Rev. 2/2009