



PF[®]-HP

HIGH PERFORMANCE SOLVENT



FEATURES

- Heavy duty, penetrating degreaser that removes grease and oil
- Specially formulated for power utility applications
- Compatible with power cable and power cable components
- Excellent for use in part washers and dip tanks
- Flash point above 140°F (60°C)
- Nonconductive
- No residue
- Does not contain chlorinated solvents
- No ozone depletion potential

PACKAGES

Net Fill

- 1 gallon (3.78 liters)
- 5 gallons (18.93 liters)
- 55 gallons (208 liters)

Part No.

- 62001
- 62005
- 62055

APPLICATIONS

- Buckets
- Cable Splices
- Cable Terminations
- Coils
- Maintenance
- Motors
- Repair Work
- Transformers
- Truck Booms
- Turbines
- Windings on Generators

PROPERTIES

Appearance/Physical State:

Colorless liquid

Boiling point:

361°F (183°C)

Evaporation Rate:

0.1 (N-butylacetate=1)

Flammable Limits (estimated):

Lower: 1.8%, Upper: 11.7%

Flash Point (TCC):

142°F – 147°F (61°C – 64°C)

HMIS

1, 2, 0

Specific Gravity (water=1):

0.85 – 0.87 @ 68°F(20°C)

Vapor Pressure:

1 mmHg at 68°F(20°C)

VOC Content:

860 g/L



MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE: WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2009 LPS Laboratories • LPS[®], PT[®] and PF[®] are registered trademarks of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2172 • Rev. 2/2009