

# SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

### 1.1 Product identifier

**Product Name:**  
**Boom Cleaning and Prewash Towels**

Product ID numbers: B-1, B-D72, B-1M

### 1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Clean and treat fiberglass boom arms

List of advices against: Not applicable.

### 1.3 Details of the supplier of the safety data sheet

#### Supplier/Manufacturer:

#### American Polywater Corporation

11222 - 60th Street North  
Stillwater, MN 55082 USA  
Tel: 1-651-430-2270  
Email: sds@polywater.com

### 1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

## 2. Hazards Identification

### 2.1 Classification of the substance or mixture

Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Flam Liq 4	H227
Skin Irrit 2	H315
Skin Sens 1	H317
Eye Irrit 2	H319

### 2.2 Label elements

Contains: d-Limonene, ethoxylated alcohols



#### Pictograms:

Signal word: Warning

#### Hazard Statements:

H227	Combustible liquid.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

#### Precautionary Statements:

P210	Keep away from flames and hot surfaces. No smoking.
------	---

P280	Wear protective gloves and eye protection.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
P337 + P313	If eye irritation persists: Get medical attention.
P370 + P378	In case of fire: Use water, fog, foam, dry chemical or carbon dioxide to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local and national regulations.

**2.3 Other hazards:** No information available.

**3. Composition/Information on Ingredients**

<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>	<u>GHS/CLP Classification</u>
d-Limonene	5989-27-5	227-813-5	< 20	Flam Liq 3, H226 Skin Irrit 2, H315 Skin Sens 1, H317 Aquatic Chronic 1, H410 Aquatic Acute 1, H400
Dimethyl glutarate	1119-40-0	214-277-2	< 15	--
Dimethyl succinate	106-65-0	203-419-9	< 10	--
Dimethyl adipate	627-93-0	211-020-6	< 10	--
Ethoxylated alcohols	68439-46-3	500-446-0	< 3	Eye Dam 1, H318

**4. First Aid Measures**

**4.1 Description of first aid measures**

- Eye Contact:** If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.
- Skin Contact:** Remove contaminated clothing; flush skin thoroughly with water. If irritation occurs, seek medical attention.
- Inhalation (Breathing):** If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention. If breathing is difficult, provide oxygen. If not breathing, give artificial respiration. Seek immediate medical attention.
- Ingestion (Swallowing):** Material has low level of oral toxicity. Ingestion of large quantities may cause irritation of the digestive tract, or nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

**4.2 Most important symptoms and effects, both acute and delayed**

Refer to Section 11 for more information.

**4.3 Indication of immediate medical attention and special treatment needed.**

No information available.

**5. Firefighting Measures**

**5.1 Extinguishing media:**

Carbon dioxide, water fog, dry chemical or foam.

**5.2 Special hazards arising from the substance or mixture**

**Hazardous decomposition and by-products:**

Burning generates CO, CO<sub>2</sub> and smoke. Smoke may be acrid and fumes irritating.

**5.3 Advice for firefighters**

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

**6. Accidental Release Measures**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Limited spill hazard with saturated towel package.

**6.2 Environmental precautions:**

Avoid release to the environment.

**6.3 Methods materials for containment and cleaning up:**

Collect towel and absorb any excess material with sand or absorbents.

**6.4 Reference to other sections:**

Refer to Sections 4, 5, 8, and 13 for more information.

**7. Handling and Storage**

**7.1 Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

**7.2 Conditions for safe storage, including incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

**7.3 Specific end uses**

See flyer on this product for further information.

**8. Exposure Controls / Personal Protection**

**8.1 Control parameters**

**Exposure limits and recommendations:**

**D-Limonene (5989-27-5)**

Country/Source	Long-term exposure limit – 8 hr TWA	Short-term exposure limit – 15 min
USA ACGIH TWA	Not established	Not established
USA OSHA PEL	Not established	Not established
Alberta, Quebec, Yukon, British Columbia, Saskatchewan, Ontario*	Not established	Not established

\* Manitoba, Newfoundland and Labrador, Nova Scotia, and Prince Edward Island are all based on the current ACGIH TLVs. New Brunswick is based on an older version ACGIH. Nunavet and Northwest Territories are based heavily on current ACGIH TLVs.

**Dimethyl glutarate (1119-40-0), Dimethyl succinate (106-65-0), Dimethyl adipate (627-93-0):**

Country/Source	Long-term exposure limit – 8 hr TWA	Short-term exposure limit – 15 min
USA ACGIH TWA	Not established	Not established
USA OSHA PEL	Not established	Not established
Alberta, Quebec, Yukon, British Columbia,	Not established	Not established

Saskatchewan, Ontario\*

\* Manitoba, Newfoundland and Labrador, Nova Scotia, and Prince Edward Island are all based on the current ACGIH TLVs. New Brunswick is based on an older version ACGIH. Nunavut and Northwest Territories are based heavily on current ACGIH TLVs.

## 8.2 Exposure controls

### Respiratory protection:

Normal ventilation is adequate. Saturated towel limits solvent vapor exposure. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH or CE approved) with particulate pre-filter, P100 or AP2.

### Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

### Eye protection:

None necessary. Wipe package eliminates splash hazard. Do not allow wipe/towel to directly contact eyes.

### Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

## 9. Physical and Chemical

### 9.1 Information of basic physical and chemical properties (bulk liquid)

<b>Appearance:</b>	Milky-white liquid with a very light citrus scent.
<b>Odor threshold:</b>	Not available
<b>pH:</b>	Not available
<b>Freezing point:</b>	Not available
<b>Boiling point:</b>	~212°F / 100°C Initial
<b>Flash point:</b>	>140°F (>60.5°C), Closed Cup (PMCC)
<b>Evaporation rate:</b>	<0.1 (n-butyl acetate = 1)
<b>Flammability (solid, gas):</b>	Not applicable to liquids
<b>Upper/lower flammability or explosive limits:</b>	Not available
<b>Vapor pressure:</b>	<1 mm Hg < 134 Pa @ 20°C
<b>Vapor density (Air = 1):</b>	Not available
<b>Specific gravity (H<sub>2</sub>O = 1):</b>	1.0
<b>Solubility in water:</b>	Dilutes emulsion
<b>Partition coefficient: n-octanol/water:</b>	Not available
<b>Auto-ignition temperature:</b>	Not available
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	Not available

### 9.2 Other Information

<b>Volatiles (Weight %):</b>	95%
<b>VOC Content:</b>	466 g/l

## 10. Stability and Reactivity

### 10.1 Reactivity:

See remaining headings in Section 10.

### 10.2 Chemical stability:

Stable

**10.3 Possibility of hazardous reactions:**

None known.

**10.4 Conditions to avoid:**

Avoid heat, flame, and sparks.

**10.5 Incompatible materials :**

Strong oxidizing agents.

**10.6 Hazardous decomposition products:**

Carbon dioxide, carbon monoxide.

**11. Toxicological Information**

**11.1 Information on toxicological effects:**

**Acute toxicity**

**Eye contact:**

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

**Skin contact:**

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

**Irritation and Sensitization Potential:**

Product may be irritating to skin and eyes. It is not a sensitizer.

**Inhalation (Breathing):**

Concentrated petroleum solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue). Persons with impaired lung function may experience additional breathing difficulties due to the irritant properties of this material.

**Ingestion:**

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

**Toxicity to Animals:**

d-Limonene: LD<sub>50</sub> (oral rat) >5000 mg/kg  
LD<sub>50</sub> (dermal rabbit) 5000 mg/kg  
RD<sub>50</sub> 1000 ppm

**Aspiration hazard**

Not considered an aspiration hazard.

**Chronic Exposure:**

**Reproductive Toxicity:** Not available.

**Mutagenicity:** Not available.

**Teratogenicity:** Not available.

**Specific Target Organ Toxicity (STOT)** No end point data.

**Toxicologically Synergistic Products:** Not available.

**Carcinogenic Status:** This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

**12. Ecological Information**

**12.1 Toxicity:**

**Ecotoxicity:** No information available.

**Aquatic Toxicity:** May be toxic to crustaceans; slow to degrade in the aquatic

environment.

- 12.2 Persistence and degradability:** No information available
- 12.3 Bioaccumulation potential:** No information available
- 12.4 Mobility in soil:** No information available.
- 12.5 Results of PBT and vPvB Assessment:** This product is not, nor does it contain a substance that is a PBT or vPvB.
- 12.6 Other adverse effects:** None known.

**13. Disposal Considerations**

Dispose of product in accordance with National and Local Regulations.

**14. Transport Information**

- UN Number:** Not Listed
- UN Proper shipping name:** Not Applicable
- Transport hazard class(es):** Not Applicable
- Packing group:** Not Applicable
- Environmental hazards:** None known
- Special precautions:** None known
- TDG:** Not Regulated
- ICAO/IATA-DGR:** Not Regulated
- IMDG:** Not Regulated
- ADR/RID:** Not Regulated

**15. Regulatory Information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**USA Federal and State**

All components are listed on the TSCA inventory.

<b>Hazard Categories for SARA Section 311/312 Reporting</b>	<u>Acute</u> Yes	<u>Chronic</u> No	<u>Fire</u> Yes	<u>Pressure</u> No	<u>Reactive</u> No
---	---------------------	----------------------	--------------------	-----------------------	-----------------------

<b>Components</b>	<b>CERCLA/SARA Sec 302 Hazardous Substance RQ</b>	<b>EHS TPQ</b>	<b>SARA Sec. 313 Toxic Release</b>
-------------------	---	----------------	------------------------------------

Components are not affected by these Superfund regulations.

<b>NFPA Ratings:</b>	Health:	1
	Fire:	2
	Reactivity:	0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

**European Union**

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list  $\geq 0.1\%$  SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

**Canada**

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

**Australia**

All components are listed on the AICS.  
Hazardous according to criteria of NOHSC Australia.

**15.2 Chemical Safety Assessment**

No chemical safety assessment has been carried out for the mixture by the supplier.

**16. Other Information**

**Abbreviations and acronyms:**

- OSHA = Occupational Safety and Health Administration
- CLP = Classification, Labeling and Packaging Regulation
- STOT = Specific Target Organ Toxicity
- LD<sub>50</sub> = Median Lethal Dose
- DNEL = Derived No Effect Level
- ACGIH = American Conference of Governmental Industrial Hygienists
- TSCA = Toxic Substances Control Act (USA)
- DSL = Domestic Substances List (Canada)
- AICS = Australian Inventory of Chemical Substances

**Mixture classification according to Regulation (EC) No 1272/2008:**

- H227 Combustible liquid.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.

**Classification Procedure**

- Physical testing
- Calculation method.
- Calculation method.
- Calculation method.

**Revision Date:** August 4, 2017

**Revision Number:** 3 NA

**Supersedes:** January 2, 2015

**Indication of Changes:** Section 1, 2, 8, 11, 16 updated. Included North American classification and exposure information.

Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Canada HPR (SOR/2015-17)(WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.