

Polywater® PedFloor™

PEDESTAL SEALING FOAM BARRIER



Polywater PedFloor burst pack installation

Creates a Hard Foam Barrier to Prevent Pest Infestation

PRODUCT BENEFITS

- **Deterrent:** Keeps rodents, snakes, and insects from entering the pedestal or cabinet.
- **Strong:** Structural foam matrix creates a strong seal.
- **Complete Seal:** Flows and self-levels before expansion to prevent ground entry.
- **Versatile:** Can be used as a suspended floor or directly on the ground.
- **Protects:** Cured product offers permanent protection through weather extremes.

Structural Barrier to Prevent Service Disruptions

Polywater® PedFloor™ Pedestal Sealant helps prevent outages and service disruptions by curing into a resilient and impermeable structural barrier. PedFloor keeps out moisture and stops pests from burrowing into the enclosure and causing costly outages or health and safety hazards.



Rodent inhabitation



Unsanitary rodent nest

polywater.com | 651-430-2270

American
Polywater[®]
Corporation

ADHESIVES | CLEANERS | LUBRICANTS | SEALANTS



PedFloor burst packs



PF-3 kit components

Convenient Kits for Easy Installation

Polywater PedFloor kits include resins, plastic containment sheet, tape, gloves, and instructions. The PF-1, PF-2, and FSTBP-200B6 are “burst packs” (*photo 1*); parts A & B are mixed in the flexible packaging after breaking the pack’s center seal. PF-3 (*photo 2*) contains premeasured containers of the two-part foam.

POLYWATER PEDFLOOR

Catalog #	Package Description	Units/Case
PF-1	1 - PedFloor burst pack (750 mL); 1 - pair of gloves; 1 - plastic sheet (per case); 1 - roll duct tape; 1 - instruction sheet Covers 1 square foot, 3 inches thick	2
PF-2	1 - PedFloor burst pack (1500 mL); 1 - pair of gloves; 1 - roll duct tape; 1 - plastic sheet; 1 - instruction sheet Covers 2 square feet, 3 inches thick	2
PF-3	1 - bottle part A; 1 - bottle part B; 1 - pair of gloves; 1 - mixing pail; 1 - mixing stick; 1 - plastic sheet; 1 - roll duct tape; 1 - instruction sheet Covers 3 square feet, 3 inches thick	1
For small repairs and/or supplemental patching, use an FSTBP™ Burst Pack:		
FSTBP-200B6	6 - FSTBP-200 (200 mL) burst packs; 6 - pairs of gloves; 1 - instruction sheet	1

SPECIFICATIONS AND APPLICATIONS:

- **Working Temperature:** PedFloor is most effective when used between 35°F (2°C) and 110°F (43°C).
- **No Application Tool:** The convenience of a burst pack ensures no application tools or accessories are necessary in the field.
- **Reaction/Curing Time:** Sealant will flow and expand for approximately 20 minutes.
- **Multiple Applications:** Bonds well to itself, ensuring multiple applications of PedFloor have the same strength as a single deployment.

CONTACT US

1-800-328-9384 Toll Free

1-651-430-2270 Main

1-651-430-3634 Fax

email: support@polywater.com

IMPORTANT NOTICE: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater’s only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from product’s use, regardless of the legal theory asserted.

American
Polywater[®]
Corporation

11222 60th Street N | Stillwater, MN 55082 USA