

Portable Hydraulic Power Packs

These portable power sources are matched perfectly to the power requirements of the Condux Fiber Optic Cable Puller and the Fiber Optic Cable Blower. Power source is a 9 HP (6.7 kW) Honda (gas), or a 16 HP (11.9 kW) Briggs & Stratton V-Twin Vanguard (gas) engine. Features electric start, large capacity hydraulic cooler, quick disconnects, low oil shut-off and 16" (406 mm) diameter pneumatic tires.



16 HP Hydraulic Power Pack
(Recommended for Fiber Puller)

| Part Number | Description |
|-------------|--|
| 08675700 | 9 HP Hydraulic Power Pack, gas (5.9 GPM @ 1800 psi) (Recommended for Fiber Blower) |
| 08675200 | 16 HP Hydraulic Power Pack, gas (8.2 GPM @ 2000 psi) (Recommended for Fiber Puller) |

| Specifications | | | | | | | | | | | | |
|---------------------------------|-------------------------------------|---|-------|------|--|-----|-----|---|-------|------|---|-----|
| Power Pack Size | 9 HP Hydraulic Power Pack | | | | 16 HP Hydraulic Power Pack | | | | | | | |
| Use Product | Fiber Optic Cable Blower | | | | Fiber Optic Cable Puller | | | | | | | |
| Part Number | 08675700 | | | | 08675200 | | | | | | | |
| Hyd. System | Open Center | | | | Open Center | | | | | | | |
| Frame Type | Two wheel mobile unit | | | | Two wheel mobile unit | | | | | | | |
| Length | 26.5 in (673 mm) | | | | 35.0 in (889 mm) | | | | | | | |
| Width | 20.0 in (508 mm) | | | | 29.0 in (736 mm) | | | | | | | |
| Height | 27.5 in (698 mm) | | | | 32.0 in (812 mm) | | | | | | | |
| Weight (Dry) | 143 lbs (64.9 kg) | | | | 233 lbs (105.6 kg) | | | | | | | |
| Filtration | 10 Micron Return Line Canister Type | | | | 10 Micron Return Line Canister Type | | | | | | | |
| Oil Cooler | Air to Oil | | | | Air to Oil | | | | | | | |
| Engine | Gas | | | | Gas | | | | | | | |
| | Honda, 9 HP (6.7 kW) @ 3,600 RPM | | | | Briggs & Stratton V-Twin Vanguard, 16 HP (11.9 kW) @ 3,600 RPM | | | | | | | |
| Fuel | 1.6 gallons/6.1 liters | | | | 5.0 gallons/18.9 liters | | | | | | | |
| Hydraulic Oil (Useable) | 5.0 gallons/18.9 liters | | | | 5.0 gallons/18.9 liters | | | | | | | |
| Hydraulic Rated Flow | GPM | @ | PSI | LPM | @ | BAR | GPM | @ | PSI | LPM | @ | BAR |
| | 6.8 | | 0 | 25.8 | | 0 | 9.1 | | 0 | 34.4 | | 0 |
| | 5.9 | | 1,800 | 22.4 | | 125 | 8.2 | | 2,000 | 31.0 | | 138 |
| Hydraulic Relief Valve Pressure | 2,150.0 PSI (148.3 BAR) | | | | 2,150.0 PSI (148.3 BAR) | | | | | | | |



9 HP Hydraulic Power Pack
(Recommended for Fiber Blower)

Hydraulic Power Pack Accessories

| Part Number | Description |
|-------------|---|
| 08675858 | Hydraulic Hose Kit, 20' (6 m) Hose with Couplings |
| 08780384 | Hydraulic Hose with flow control manifold |
| 02260000 | Hydraulic Coupling, Female Flat Face Faster 2FFN38-12NPT-F / Bruning FF371-8FP |
| 02260100 | Hydraulic Coupling, Male Flat Face Faster 2FFN38-12NPT-M / Bruning FF372-8FP |
| 02260200 | Dust Cap, Male Coupling |
| 02260201 | Dust Cap, Female Coupling |
| 02286416 | Power cord assembly extension, 2-pin straight, 20' (6 m) |
| 08761248 | Power cord with cigarette adapter |



Dust Caps

Couplings

FIBER CABLE
INSTALLATION