



WDR505 CABLE PULLER

Hydraulic Underground Cable Pulling Trailer Kits w/Compressor

Part Number	Description
08763230	WDR505 Underground Pulling Trailer with Compressor
08763230-1	WDR505 Underground Pulling Trailer with Compressor & Electronic Control Box
08763230-1R	WDR505 Underground Pulling Trailer with Compressor & Electronic Control Box & Remote
08763230R	WDR505 Underground Pulling Trailer with Compressor & Remote

NYLATRON®* ROLLERS have a super-hard surface and last longer than conventional cast rollers.

*Nylatron is a registered trademark of DSM.

FULLY ENCLOSED UNIT features separate door for operating controls. The WDR505 is safe, convenient and reliable.

AUTOMATIC PAY-IN AND PAY-OUT offers more operator control and safety.

ROTATING ARM pivots 15° in either direction aligning easily and accurately.

DYNAMOMETER INTEGRATED IN THE PULLER unit to control pull limits to cable manufacturer specs. Automatically adjusts pull speed to limit pull load during pull.

TANDEM AXLE TRAILER for easy maneuvering on job sites.

NOISE ATTENUATED ENGINE COMPARTMENTS for quiet operation on urban job sites.

HYDRAULIC PULLER UNITS WITH OIL COOLER provide smooth operation throughout the pull.

POWER CABLE
INSTALLATION

WDR505 CABLE PULLER



DIESEL ENGINE provides 45 HP and features easy access maintenance. Water cooled.

STRAIGHTFORWARD OPERATOR CONTROLS allow equipment operator to safely operate the puller with a very short training period.

QUIET, PLEASE
Noise is reduced due to the self-contained design of the cable puller trailer, and especially because of extensive use of noise abating materials in the engine surround and control panel covers. Adds comfort and safety to your jobs.



AIR COMPRESSOR rated at 185 CFM at 100 psi, 20 gallon diesel fuel tank.

ON BOARD TOOLBOX is also fully enclosed.

ELECTRIC BRAKES with a 7 pin round connector standard.



TRAILER GROUND CLEARANCE
16 inches.

DOT CERTIFIED TRAILER

POWER CABLE
INSTALLATION

SPECIFICATIONS

MAX LINE PULL, POUNDS	11,250
SPEED AT CONTINUOUS PULL, POUNDS	9,000
HIGH SPEED CONTINUOUS PULL, POUNDS	2,250
PULLING SPEED FEET PER MINUTE	0-219
BULL WHEEL DIA., INCHES	13
MAX ROPE DIA., INCHES	1/2
FEET OF ROPE	2,600
ENGINE TYPE	DIESEL
HORSEPOWER	45
ELECTRICAL SYSTEM	12 Volt
TRAILER LENGTH, INCHES	252
TRAILER WIDTH, INCHES	77
TRAILER HEIGHT, INCHES	114
WEIGHT, POUNDS	8,500